NPT75 SERIES CASTOR

本體及煞車踏板採用Nylon加上特殊配方，腳架旋轉頸部及輪子採用精密軸承。輪子有TPU材質與TPR可供選擇。
Glass fiber reinforced Nylon 6 for body and brake pedals, precision ball bearings swivel head and wheel axles. Non-marking, elastic thermoplastic polyurethane treads.

P 方盤結構 Top Plate Fitting

Total locking

Catis code	mm	mm		Fitting	mm	mm	mm	kg	Shore A	kg
NPT75BP2/G	75	25	●●	P2	25	106	98	50.0	70±5	0.39

Free swivel

Catis code	mm	mm		Fitting	mm	mm	mm	kg	Shore A	kg
NPT75P2/G	75	25	●●	P2	25	106	84	50.0	70±5	0.37

- 輪胎硬度 Durometer of tire
- 荷重 根據EN12526 ~EN12533規範，定義每顆腳輪荷重(公斤)
  Load Capacity as determined per EN12526 to EN12533, Load Capacity / Per Castors (kgs)
- ●● 精密軸承 Precision ball bearing



P2

- 另外有導電輪可供選擇。
  Conductive wheels are also available
- 另外有不鏽鋼腳輪可供選擇。
  Stainless steel castors are also available.

T 螺牙式結構
Threaded Stem Fitting with Hex Base Washer

Total locking

Catis code	mm	mm		Fitting	mm	mm	mm	kg	Shore A	kg
NPT75BT2/G	75	25	●●	T2	25	106	98	50.0	70±5	0.31
NPT75BT3/G	75	25	●●	T3	25	106	98	50.0	70±5	0.31
NPT75BT4/G	75	25	●●	T4	25	106	98	50.0	70±5	0.31

Free swivel

Catis code	mm	mm		Fitting	mm	mm	mm	kg	Shore A	kg
NPT75T2/G	75	25	●●	T2	25	106	84	50.0	70±5	0.29
NPT75T3/G	75	25	●●	T3	25	106	84	50.0	70±5	0.29
NPT75T4/G	75	25	●●	T4	25	106	84	50.0	70±5	0.29

- 輪胎硬度 Durometer of tire
- 荷重 根據EN12526 ~EN12533規範，定義每顆腳輪荷重(公斤)
  Load Capacity as determined per EN12526 to EN12533, Load Capacity / Per Castors (kgs)
- ●● 精密軸承 Precision ball bearing



Code	Dimension
T2	1/2-13UNC×1"
T3	M10×25mm P=1.5
T4	M12×25mm P=1.75

- 另外有導電輪可供選擇。
  Conductive wheels are also available
- 另外有不鏽鋼腳輪可供選擇。
  Stainless steel castors are also available.